



HOBO[®] RXW-SMD-xxx Sensor

HOBOnet Soil Moisture 10HS Sensor

The HOBOnet Wireless Soil Moisture Sensor integrates the field-proven ECH2O™ 10HS Sensor and provides readings directly in volumetric water content. The 10cm probes measure soil moisture over a larger volume of soil, helping to average out any soil variability. The sensor's high-frequency design minimizes sensitivity to salinity and textural effects, and gives it a wide measurement range. HOBOnet Wireless Sensors communicate data directly to the RX3000 weather station or pass data through other wireless sensors back to the central station. They are preconfigured and ready to deploy, and data is accessed through HOBOLink, Onset's innovative cloud-based software platform.



Supported Measurements:

Soil Moisture

Key Advantages:

Sensor Features

- $\pm 3\%$ accuracy in typical soil conditions, and $\pm 2\%$ accuracy with soil-specific calibration
- Measures a large 1-liter volume of soil, providing a more accurate picture of average soil moisture
- High-frequency (70 MHz) circuit provides good accuracy even in high-salinity and sandy soils.

Wireless Features

- 900 MHz wireless mesh self-healing technology
- 450 to 600 meter (1,500 to 2,000 feet) wireless range and up to five hops
- Up to 50 wireless sensors per RX3000
- Simple button-push to join the HOBOnet wireless network
- Onboard memory to ensure no data loss
- Powered by rechargeable AA batteries and built-in solar panel

HOBO RXW-SMD-xxx Sensor Specifications

Sensor

| | |
|----------------------------|--|
| Measurement Range | In soil: 0 to 0.570 m /m (volumetric water content) |
| Extended Range | -0.659 to 0.6026 m /m ; see Note 1 |
| Accuracy | ±0.033 m /m (±3.3%) typical 0 to 50°C (32° to 122°F) for mineral soils up to 10 dS/m and ±0.020 m /m (±2%) with soil specific calibration; see Notes 4 and 5 |
| Resolution | 0.0008 m /m (0.08%) |
| Volume of Influence | 1 liter (33.81 oz) |
| Sensor Frequency | 70 MHz |

Sensor Operating Temperature Range 0° to 50°C (32° to 122°F). Although the sensor probe and cable can safely operate at below-freezing temperatures (to -40°C/F), the soil moisture data collected at these extreme temperatures is outside of the sensor's accurate measurement range. Extended temperatures above 50°C (122°F) will decrease mote battery life.

Wireless Mote

| | |
|------------------------------------|---|
| Operating Temperature Range | -25° to 60°C (-13° to 140°F) with rechargeable batteries -40 to 70°C (-40 to 158°F) with lithium batteries |
| Radio Power | 12.6 mW (+11 dBm) non-adjustable |
| Transmission Range | Reliable connection to 457.2 m (1,500 ft) line of sight at 1.8 m (6 ft) high Reliable connection to 609.6 m (2,000 ft) line of sight at 3 m (10 ft) high |
| Wireless Data Standard | IEEE 802.15.4 |
| Radio Operating Frequencies | RXW-SMD-900: 904–924 MHz RXW-SMD-868: 866.5 MHz RXW-SMD-922: 916–924 MHz |
| Modulation Employed | OQPSK (Offset Quadrature Phase Shift Keying) |
| Data Rate | Up to 250 kbps, non-adjustable |
| Duty Cycle | <1% |
| Maximum Number of Motes | 50 motes per one RX Wireless Sensor Network |
| Battery Type/ Power Source | Two AA 1.2V rechargeable NiMH batteries, powered by built-in solar panel or two AA 1.5 V lithium batteries for operating conditions of -40 to 70°C (-40 to 158°F) |
| Battery Life | With NiMH batteries: Typical 3–5 years when operated in the temperature range -20° to 40°C (-4°F to 104°F) and positioned toward the sun (see Deployment and Mounting), operation outside this range will reduce the battery service life With lithium batteries: 1 year, typical use |
| Memory | 16 MB |
| Dimensions | RXW-SMD-xxx soil probe: 89 x 15 x 1.5 mm (3.5 x 0.62 x 0.06 in.) Cable length: 5 m (16.4 ft) Mote: 16.2 x 8.59 x 4.14 cm (6.38 x 3.38 x 1.63 inches) |
| Weight | RXW-SMD-xxx sensor and cable: 180 grams (6.3 oz) Mote: 223 g (7.87 oz) |
| Materials | Sensor: Weatherproof Mote: PCPBT, silicone rubber seal |
| Environmental Rating | Mote: IP67, NEMA 6 |
| Compliance Marks |  RXW-SMD-900  RXW-SMD-868  RXW-SMD-922 |

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532